

## Светильник MD120-6W Warm White



### FEATURES

1. Adopt 2835 LED as light source, high lumen
2. The highest class Aluminium alloy, thermal conductivity
3. PMMA diffuser, high transmittance
4. Special designed LGP, glare-free, ensure superior light uniformity
5. Environmental friendly, Lead and Mercury free
6. Instant start-up

### APPLICATION

Commercial lighting & Jewelry counter; Institution Buildings & Hospitals  
 Schools, Colleges, Universities, Residential; Factories & Offices  
 Restaurant, hotel; Amusement park, Artwork lighting, Display case etc.

### SPECIFICATION

Parameters	Description	
Material	Aluminum+Acrylic LGP+Acrylic cover	
Lamp body color	Silver	
LED	SMD3014	
LED QTY	60pcs	
Input Voltage	100-240VAC (±10%) 50/60Hz	
Power	6W	
CCT	3000K	
Lumen	300-450lm	
CRI	≥75	
Beam Angle	120°	
Lifespan	50000hrs	
Lumens depreciation	5000 hours<6%; 30000 hours<25%	
Operation Temperature	-20°C ~ +40°C	
Lamp dimension	Φ122.5*16mm	
Cutting Hole	Φ110mm	
Net weight	0.15kg	
Certificate	CE, RoHS, FCC	
Socket	Terminal	
Dimmable or not	Optional	
LED Driver (included) 6w	Rated value	Input: 100-240VAC 50Hz/60Hz
	Limited value	Input: 90-264VAC 50Hz/60Hz
Installation	Embedded	