

Светильник MD120-6W Day White



FEATURES

1. Adopt 2835 LED as light source, high lumen
2. The highest class Aluminium alloy, thermal conductivity
3. PMMA diffuser, high transmittance
4. Special designed LGP, glare-free, ensure superior light uniformity
5. Environmental friendly, Lead and Mercury free
6. Instant start-up

APPLICATION

Commercial lighting & Jewelry counter; Institution Buildings & Hospitals
 Schools, Colleges, Universities, Residential; Factories & Offices
 Restaurant, hotel; Amusement park, Artwork lighting, Display case etc.

SPECIFICATION

| Parameters | | Description |
|--------------------------|---------------|------------------------------------|
| Material | | Aluminum+Acrylic LGP+Acrylic cover |
| Lamp body color | | Silver |
| LED | | SMD3014 |
| LED QTY | | 60pcs |
| Input Voltage | | 100-240VAC ($\pm 10\%$) 50/60Hz |
| Power | | 6W |
| CCT | | 4000K |
| Lumen | | 300-450lm |
| CRI | | ≥ 75 |
| Beam Angle | | 120° |
| Lifespan | | 50000hrs |
| Lumens depreciation | | 5000 hours<6%; 30000 hours<25% |
| Operation Temperature | | -20°C ~ +40°C |
| Lamp dimension | | $\Phi 122.5 \times 16$ mm |
| Cutting Hole | | $\Phi 110$ mm |
| Net weight | | 0.15kg |
| Certificate | | CE, RoHS, FCC |
| Socket | | Terminal |
| Dimmable or not | | Optional |
| LED Driver (included) 6w | Rated value | Input: 100-240VAC 50Hz/60Hz |
| | Limited value | Input: 90-264VAC 50Hz/60Hz |
| Installation | | Embedded |