

Светильник MD180-10W White

FEATURES

1. Adopt 2835 LED as light source, high lumen
2. The highest class Aluminium alloy, thermal conductivity
3. PMMA diffuser, high transmittance
4. Special designed LGP, glare-free, ensure superior light uniformity
5. Environmental friendly, Lead and Mercury free
6. Instant start-up



APPLICATION

Commercial lighting & Jewelry counter; Institution Buildings & Hospitals
Schools, Colleges, Universities, Residential; Factories & Offices
Restaurant, hotel; Amusement park, Artwork lighting, Display case etc.

SPECIFICATION

Parameters		Description
Material		Aluminum+Acrylic LGP+Acrylic cover
Lamp body color		Silver
LED		SMD3014
LED QTY		96pcs
Input Voltage		100-240VAC (±10%) 50/60Hz
Power		10W
CCT		6000K
Lumen		600-710lm
CRI		≥75
Beam Angle		120°
Lifespan		50000hrs
Lumens depreciation		5000 hours<6%; 30000 hours<25%
Operation Temperature		-20°C ~ +40°C
Lamp dimension		Φ177.8*16mm
Cutting Hole		Φ170mm
Net weight		0.34kg
Certificate		CE, RoHS, FCC
Socket		Terminal
Dimmable or not		Optional
LED Driver (included) 6w	Rated value	Input: 100-240VAC 50Hz/60Hz
	Limited value	Input: 90-264VAC 50Hz/60Hz
Installation		Suspended/Embedded